



The Testcenter facility 'LoRa® Test Lab' within IMST GmbH is recognized by the LoRa™ Alliance for testing in accordance to the LoRaWAN™ Specification V1.0.2

Report for Test of Conformance to LoRaWAN™ V1.0.2

for the Device

“Clickey Comfort Sensor v2.4”

for the Customer

“Clickey Solutions B.V.”

Markus Ridder

Yavuz Turan

09. Mar. 2018

Administrative Summary

Location: IMST GmbH, Test Centre, Kamp-Lintfort, Germany

Responsible Test Engineer: Yavuz Turan, Markus Ridder

Subject: Test of Conformance to LoRaWAN™ Specification V1.0.2

Company and Contact Information:

Clickey Solutions B.V.

Mr. Pedro de Smit

Langebroekstraat 3, 4944XH Raamsdonk

Netherlands

Tested Device: Clickey Comfort Sensor v2.4

Firmware version: V1.0

Hardware version: V3.0

End-device identifier: 96011a0000ac5900

LoRa Device Class: A

LoRaWAN Specification version: V1.0.2

Certification requirements: LoRa End Device Certification EU Version 1.5

Frequency band(s) tested: 868 MHz

Test Equipment: Test Software Version: 1.1.11

Semtech IOT SX1301 Starter Kit: Gateway software version 3.1.0

Packet forwarder software version 2.1.0

Test Result: PASS

Chief Test Engineer: Markus Ridder
Dept. Test Center

Date: March 9nd, 2018

The Test Report, No. 6180390 has the following conclusion:

The device has PASSED the tests hereunder.

Responsibility: 

Yavuz Turan
Test Engineer

Approved: 

Markus Ridder
Quality Engineer

Copyright Notice & Disclaimer: No part of this test report may be reproduced without written permission of IMST GmbH. The test results herein only refer to the tested sample. IMST GmbH cannot be made responsible for any generalizations or conclusions drawn from the test results presented herein concerning further samples of the tested device. Modification of the tested sample(s) is prohibited and leads to invalidity of this report.

1 Description of the Device Under Test (DUT)

1.1 General

Item	Value
Product name	Clickey Comfort Sensor v2.4
Kind of product	Smart Building device
Series (if any)	
Hardware Version	V3.0
Firmware Version	V1.0
Type of DUT	<input checked="" type="checkbox"/> Module / End Device <input type="checkbox"/> Gateway / Concentrator
Geographical area of operation	<input checked="" type="checkbox"/> Europe <input type="checkbox"/> USA
Operating frequency	<input type="checkbox"/> 433 MHz <input checked="" type="checkbox"/> 868 MHz <input type="checkbox"/> 915 MHz
Adaptive Data Rate (ADR) supported?	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No
Optional data rates supported?	<input type="checkbox"/> DR6 <input type="checkbox"/> DR7
Activation possibilities	<input type="checkbox"/> Over the air <input type="checkbox"/> by personalization <input checked="" type="checkbox"/> both
Test According LoRaWAN™ Spec	<input type="checkbox"/> V1.0.1 <input checked="" type="checkbox"/> V1.0.2
Output Power	2 to 14dBm
Number / Type of Antenna(s)	1 / Internal Wire Antenna
Antenna Gain	3 dBi

Table 1 Device Information

1.2 DUT Modes of Operation

During the tests the device operated in the following modes:

- Test mode according to document “LoRa End Device Certification EU V1_5” Chapter 3.

1.3 DUT Setup




Figure 1 DUT Setup

Applied Methods of Measurement

1.4 Protocol Testing according to LoRaWAN™ specification V1.0.2

Detailed Test Results:

Test Mode Activation (Activation By Personalization): **PASS**

Test Mode Activation (Over the Air Activation): **PASS**

Test Application Functionality: **PASS**

Packet Error Rate RX2 SF12: **PASS**

Cryptography: **PASS**

Downlink Window Timing: **PASS**

Frame Sequence Number: **PASS**

Device Status Request: **PASS**

Mac Commands: **PASS**

New Channel Request: **PASS**

Confirmed packets: **PASS**

RX Parameter Setup Request: **PASS**

RX Timing Setup Request: **PASS**

Link ADR Request: **PASS**

Packet Error Rate RX1 Window: **PASS**

Packet Error Rate RX2 Window: **PASS**

Supported Optional Features:

Adaptive Data Rate (ADR): Yes

DR6 (SF7BW250): No

DR7 (FSK50): No

Link ADR Request Block: No

Di Channel Request: Yes

Range 6 dB: Yes

Remarks: None.

Result: The device passed the test without limitations.